

28-Port 10-gigabit Combo POE Managed Industrial Ethernet Switch



- 16 fixed 10/100/1000M Ethernet ports; rate self-adaption, full/half duplex mode, MDI/ MDI-X self-adaption;
- 8 fixed 10/100/1000M Combo (SFP slot or RJ45)
- 4 fixed 10000M SFP+ interfaces, Supports the 10GBASE-KR/CR/LR/SR specification of optical fiber 10-Gigabit Ethernet;
- 16 Ethernet ports support the standard POE function and support the IEEE 802.3at/af standard. The total power cannot exceed 300W;
- Support Web, CLI and SNMP three management modes, and CLI supports Telnet and console log in;
- Support QoS, IGMP, 802.1Q VLAN function ;
- Support RSTP and CK-Ring for Ethernet redundancy;
- Support relay alarm output for power supply, port and ring network status alarm;
- Support wide range voltage 90~264V AC single power input(128V DC ~ 370V DC optional);
- Adopt with high strength IP40 housing and industrial EMC design;
- Working temperature range: -40~85℃, meet various industrial site requirements

Product Overview

28-Port 10-gigabit Combo Managed Industrial Ethernet switch adopts with high strength IP40 protective housing, industrial EMC design. It's layer 2 Ethernet switches independently developed by Shenzhen Comark Technology Co., Ltd., provide powerful management functions, which can be managed through Web browser, command line (CLI) and SNMP. The product provides 16 fixed 10/100/1000M self-adaptive Ethernet ports, 8 fixed 10/100/1000M Combo (SFP slot or RJ45), 4 fixed 10000M SFP+ interfaces. The 16 Ethernet ports support the standard POE function and the IEEE 802.3at/af standard. The total power cannot exceed 300W .Base on industrial installation requirements, provide 1U standard rack mounting installation mode. The product also adopts with fan-free, low power consumption, industrial design, working temperature range of - 40 ~ 85℃, which can meet the requirements of various industrial sites, and provide convenient Ethernet communication solutions.

Features

Basic Switching Features

- Conform to IEEE802.3/802.3u /802.3ab/802.3z standard, store and forward switching
- Provide 16 fixed 10/100/1000M self-adaptive Ethernet ports, Auto MDI/MDIX
- Provide 8 fixed 10/100/1000M Combo (SFP slot or RJ45)
- Provide 4 fixed 10000M SFP +interfaces, Supports the 10GBASE-KR/CR/LR/SR specification of optical fiber 10-Gigabit Ethernet
- The 16 Ethernet ports support the standard POE function and the IEEE 802.3at/af standard. The total power cannot exceed 300W
- Adopt with high strength IP40 housing and industrial EMC design
- Support wide range voltage 90~264V AC power input
- Support wide range voltage 128V~370V DC power input
- -40~85℃ working temperature range
- CLI supports Telnet and Console log in
- Support store and forward mechanism
- Support common port feature settings, such as port enabling, adaptive or forced, flow control, etc
- Support port mirroring for online debugging and monitoring of network data status
- Support the function of port bandwidth limitation and optimize bandwidth utilization
- support port aggregation function to expand network bandwidth and improve network transmission efficiency.
- Support port priority QoS settings to improve network service quality
- Support port MAC address learning and data statistics functions
- Support 802.1Q VLAN setting and effectively control broadcast domain
- Support unicast / multicast MAC address management
- Support static IGMP multicast filtering, which is used to filter the multicast traffic in the industrial Ethernet protocol.

Advanced Industrial Redundant Ethernet Network

Features

- Support Web, CLI and SNMP three management modes,

- Support broadcast storm suppression function
- Support SNMP V1 / V2C / V3 to make different levels of network management secure
- Support RSTP to avoid message proliferation and infinite loop in the loop network

- supports plug and play redundant self-healing Ethernet ring network technology, and supports three ring network modes: single ring, tangent and intersection.
- Support relay alarm output
- Support the whole network system management

Specification

Technology

- Standard: IEEE802.3、IEEE802.3u、IEEE 802.3ab、IEEE 802.3z、IEEE802.3x、IEEE802.1Q、IEEE802.1p、IEEE802.1d、IEEE802.1w

Interfaces

- RJ45 port:10/100/1000BASE-T rate self-adaption, Full/half duplex mode, MDI/MDI-X self-adaption.
- SFP interfaces:1000M SFP/10000M SFP+(Supports twisted pair transmission)
- Console: RS-232 (RJ45 connector) debugging serial ports

Exchange Property

- 10M forwarding speed:14881pps
- 100M forwarding speed:148810pps
- 1000M forwarding speed:1488096pps
- 10000M forwarding speed:14880960pps
- Transmission way:Store and forward.
- System switching bandwidth:128Gbps
- Cache size:1.5Mbits
- MAC address table:16K

Power Supply

- Alternating current power supply: wide range voltage

90~264V AC(50~60Hz 1.2A) power input, with three-wire single-phase power cord

- Direct-current power supply: redundant wide range voltage 128~370V DC power input, with 4 cores 7.62mm spacing industrial terminal, power supply supports reverse connection protection and non polarity function

Relay

- Relay alarm output: alarm output of port failure, power failure and ring network failure
- Max. contact capacity:1A@24VDC

Mechanical Properties

- Dimension(W×H×D): 440mm×44mm×274mm
- Net weight: 3.15 Kg
- Housing: IP40 protection, metal housing
- Installation:1U standard rack installation

Operating Environment

- Working temperature:-40℃~85℃
- Storage temperature: -40℃~ 85℃
- Relative humidity: 5% ~ 95% (no condensation)


Warranty

- Warranty: 5 years

Standard

- IEC61000-4-2(ESD): ±8KV Contact Discharge, ±15KV Air Discharge
- IEC61000-4-3(RS): 10V/M (80-1000MHZ)
- IEC61000-4-4(EFT): Power Cable ±4KV, Data Cable ±4KV
- IEC61000-4-5(Surge): Power Cable ±4KV CM/±2KV DM, Data Cable: ±4KV
- IEC61000-4-6(Radio Frequency Conduction): 3V (10KHZ-150KHZ), 10V (150KHZ-80MHZ)
- IEC61000-4-16(Common Mode Conduction) : 30V(cont.),300V(1s)
- IEC60068-2-6 (Vibration)
- IEC60068-2-27 (Shock)
- IEC60068-2-32 (Free fall)
- IEC61000-6-2(General Industrial Standards), IEC61850-3(Transformer Substation), IEEE1613(Power Substation)
- EN50121-4(Rail Transit)

Dimension(mm)



Product Models

Product Models	Specification & Descriptions
CRS8028MP-16GT X8GC	Industrial Managed POE Switch,16*10/100/1000M self-adaptive Ethernet ports(POE), 8 fixed 10/100/1000M Combo (SFP slot or RJ45) ,4*10000M SFP+ interfaces,1U standard rack installation,-40℃~85℃

Package List

- 28-Port 10-gigabit Combo POE Managed Industrial Ethernet Switch 1pcs (with power cable and debugging serial port wire)
- Product Manual 1pcs